

USB CONFIG DEVICE AND SOFTWARE

The small, compact USB config device offers operators of small and mini locking systems the opportunity of maintaining complete control over the locking system at an affordable price. It enables them to create a locking system, programme components and manage access authorisations. The USB config device is offered in combination with an easy-to-use administration software.

The LSM Starter locking plan administration software contains a matrix screen from which all other dialogues can be opened with just a click of the mouse. For typical standard tasks such as saving a new transponder or configuring a new door there are intuitive wizards or a simple one-click solution.



TECHNICAL SPECIFICATIONS FOR USB CONFIG DEVICE.

- :: Programming: SimonsVoss Active Technology, 25 kHz
- :: LSM version: LSM 3.2 SP1 or higher
- :: Operating system: Windows XP SP3 or higher
- :: USB port: USB type A (same as a flash memory) / USB 2.0
- :: Power supply: USB socket
- :: Dimensions: W x H x D (57)70 x 19 x 13 mm
- :: Programming distance: 10-30 cm
- :: Protection category: IP40
- :: Temperature range: -10°C to + 60°C
- :: Humidity: 95% (non-condensing)

ORDER CODE.

USB programming device to programme SimonsVoss products.
Connection to a PC via USB port in conjunction with LSM Starter

CD.STARTER.G2

TECHNICAL DATA OF LSM STARTER SOFTWARE.

- :: Supported operating systems: Windows XP, Vista, Windows 7 and Windows 8
- :: Mounted database: ADS
- :: No. of doors: max. 20
- :: No. of media: max. 100
- :: Upgrade to LSM Basic, LSM Business and LSM Professional Edition possible at any time

ORDER CODE.

LSM Starter locking plan administration software for installation on a PC / laptop, operating system: Windows XP SP3 or higher LSM.STARTER